


Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Pebble, Pewter, Nickel, Limestone & Porcelain
Product Code	-
Format	20.133 Knockout
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	12.5
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.57
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Pebble, Porcelain, Nickel, Pewter & Limestone
Product Code	-
Format	10.109 Solid Half Height
Place of Manufacture	-
Length (mm)	390
Width (mm)	90
Height (mm)	100
Size	390x100x90
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	25
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.57
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Limestone, Pewter, Pebble, Porcelain & Nickel
Product Code	-
Format	10.971 Half Height
Place of Manufacture	-
Length (mm)	390
Width (mm)	90
Height (mm)	90
Size	390x90x90
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	25
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.39
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Pewter, Porcelain, Pebble, Nickel & Limestone
Product Code	-
Format	20.139 Corner
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	12.5
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.84
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Limestone, Pebble, Nickel, Pewter & Porcelain
Product Code	-
Format	20.121 Standard
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	12.5
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.39
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Porcelain, Pewter, Nickel, Pebble & Limestone
Product Code	-
Format	20.127 Half Height
Place of Manufacture	-
Length (mm)	390
Width (mm)	90
Height (mm)	190
Size	390x190x90
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	25
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.41
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Pewter, Limestone, Nickel, Pebble & Porcelain
Product Code	-
Format	10.91 Standard
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	90
Size	390x90x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	12.5
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.84
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-


Notes

-

Product Details

Product Range	GB Split Face
Texture Finish	
Colours	Porcelain, Limestone, Nickel, Pebble & Pewter
Product Code	-
Format	10.125 Corner Return
Place of Manufacture	-
Length (mm)	390
Width (mm)	190
Height (mm)	190
Size	390x190x190
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	-
Units Per Tonne	-
Units Per Pallet	-
Units per Square Metre	-
Durability Class	-
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	0.41
LRV	-
FRL	-
EPD	No
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

-