


Range: San Selmo Corso

Colour:

SKU: 9B0570232160001970150



Technical Data

| | |
|--|---------|
| Width (mm) | 100 |
| Height (mm) | 40 |
| Depth (mm) | 500 |
| Dimensional Category | DW0 |
| Average Weight / Unit (kg) | 3.2 |
| Core Volume (%) | Solid |
| Units per Square Metre | 40.8 |
| Characteristic Unconfined Compressive Strength (f 'uc) MPa | >10 |
| Maximum Cold Water Absorption (%) | 25 |
| Initial Rate of Absorption (IRA) (kg/m2 min) | 1.0-8.0 |

| | |
|--|---------------|
| Coefficient of Expansion e'Factor (mm/m) | 1.2 |
| Liability to Efflorescence | Nil to slight |
| Lime Pitting Liability | Nil to slight |
| Solar Absorption | 0.73 |
| LRV | 9.2 |
| Basix | Medium |
| Place of Manufacture | Italy |
| Product Warranty | 100 Years |
| Solar Absorption | 0.73 |
| Meter squared | 40.8 |

This Data represents average results from commercial production lots. If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NSZ 4456 ARE USED AS APPLICABLE. January 2025

www.brickworks.co.nz

A BRAND OF

BRICKWORKS